






SECURITY GRATES

Model GR-A1 - Security Grates with round bars in angle frame




OPTIONAL CORNERS

Open



Mitered



QTY	FRAME W	FRAME H	TAG

STANDARD CONSTRUCTION:

A-36 steel frame with continuously welded seams and notched corners.

A-36 steel round bars 6" o.c.. both ways welded to frame and at intersections.

Two part polyurethane inside and out. White.

Minimum size 4" x 4". Maximum single piece size is 72" x 48". Larger sizes will ship in multiple sections with full frames for field butting. Masonry opening = frame O.D. + 1/4".

OPTIONS

FRAME SIZING

- O.D. undersized 1/4" (Std)
- Exact O.D.

FRAME MATERIAL

- A-36 steel (Std)
- Type 304 stainless steel
- Type 316 stainless steel
- Other _____

FRAME SIZE

- 2-1/2" x 2-1/2" x 1/4" (Std)
- 2" x 2" x 1/4"
- Other _____

FRAME CORNERS

- Open (Std)
- Notched
- Mitered

BAR MATERIAL

- A-36 hot rolled steel (Std.)
- 1018 alloy cold rolled steel
- 1045 alloy steel
- Type 304 stainless steel
- Type 316 stainless steel
- Other _____

BAR SIZE

- 1/2" Dia. (#4) (Std)
- 5/8" Dia. (#5)
- 3/4" Dia. (#6)
- 7/8" Dia. (#7)
- 1" Dia. (#8)
- Other _____

BAR CENTERS

- 6" o.c. both ways (Std.)
- Vertical bars _____" o.c.,
- Horizontal bars _____" o.c.

FINISH

- Two part Polyurethane white (Std.)
- Mill finish - stainless steel only
- Other _____

BOLT HOLES

- None (Std)
- 5/16" dia. holes. 6" o.c., minimum one per side. No bolts.
- Other size or spacing _____

To maintain our policy of continuous product development, we reserve the right to change prices, specifications, ratings, and dimensions without notice or obligation.

Project/Location		KEES INCORPORATED 400 South Industrial Drive Elkhart Lake, WI 53020 Ph: 920.876.3391 F: 920.876.3065 www.kees.com	
Engineer/Architect			
Contractor			
Representative			
		Date	